

233 EUROSOL CONTACT

Two-sided contact adhesive.



Product Typification

Basis : Synthetic rubber in solvent.
Colour : Cream.
Consistency : Thick liquid.

- High initial adhesion strength
- Fast drying
- High final bond strength
- Favourable spreading capacity

Performances

Specific weight : 0.85 kg/l.
Flammability : 233 Eurosol Contact contains a highly flammable solvent. Do not smoke during application, do not expose to open flame, extinguish pilot lights and ventilate thoroughly.
Consumption : 200 - 250 g/m², when fixed two-sided.

Application

For the two-sided installation of:

- rubber
- homogeneous PVC
- plastic profiles
- linoleum
- leather, board, cork
- carpet
- foam-rubber.

Working Process

Storage : Protect against high temperatures.
Tools : Adhesive spreader A4 or brush.
Open time : 1 uur.*
Latency : 15 minutes.*
Drying : 12 hours.*
Shelf Life : 6 months, in unopened packaging.

* The mentioned values have been established in our laboratory and must be considered as guidelines in view of possible variations in climatic circumstances, subfloor compositions and layer thickness.

Substrate:

- 233 Eurosol Contact is suitable for any type of subfloor that has a good tensile and compression strength. The subfloor should also be clean, permanently dry and free from grease and dirt, according to the requirements of BS 8203 or DIN 18 365.
- In advance always seek our technical data sheets. In doubt about the application ask for technical advice.

User manual:

Working conditions:

Required surrounding temperature : 18° - 23 °C.

Material and subfloor temperature : min. 15° - max. 20 °C.

Relative humidity : 40 - 80%.

Directions for use:

- Shake the adhesive well before use.
- Apply the adhesive on the subfloor and back of the material to be fixed with a brush or adhesive spreader A2.
- Allow the adhesive to dry for 15 minutes (depending on temperature, relative humidity, subfloor and material).
- Place the material on the subfloor and press, roll or hammer firmly.
- After mixing adjustments are not longer possible.
- Remove fresh spots immediately with white spirit.
- Do not smoke during application, do not expose to naked flame, extinguish pilot lights and ventilate thoroughly.

Underfloor heating systems:

233 Eurosol Contact can be applied on underfloor heating systems. The startprotocol of the floorheating needs to be completely executed in accordance with the directives of the supplier. Turn off the heater 24 hours before application. Do not heat again until at least 24 hours after installation, in steps of 5 °C per day.

Environment and health

Hazard Class : 3-5c ADR/VLG-adhesives/ UN-code 1133.

Safety and environment : Safety data sheets of Forbo Eurocol products according to EEG-guideline 91/155.

MSDS : For extensive information about safety and environment we refer to our website www.eurocol.nl.

Articles

Article	Definition	Packaging	EAN-code
233	Eurosol Contact	10 liter metal drum	8 710345 233057
233	Eurosol Contact	5 litre metal drum	8 710345 233095
233	Eurosol Contact	0.75 litre metal drum	8 710345 233071